This listing of claims will replace all prior versions and listings of claims in the

application:

Listing of Claims:

Claim 1 (original): A process for producing a pigmented paint layer of a dry-paint film for

application to a component, the dry-paint film including a support material and at least one

pigmented paint layer, the process including:

applying a first layer to the support material having a first dry layer thickness of between

10 and 50 µm by at least one of knife coating, rolling, pouring or printing; and

applying a second layer having a second dry layer thickness to the first layer by

atomization, wherein the first dry layer thickness is greater than the second dry layer thickness

by a factor of from 3 to 5.

Claim 2 (original): The process as recited in claim 1, further comprising applying a transparent

top layer to the second layer.

Claim 3 (original): The process as recited in claim 2, wherein the transparent top layer is formed

by UV-curing varnish.

Claim 4 (original): The process as recited in claim 1, wherein the applying of the second layer is

performed in a wet-on-wet operation, before the first layer has dried.

Claim 5 (original): The process as recited in claim 1, wherein the applying of the second layer is

performed after the first layer has dried.

Claim 6 (original): The process as recited in claim 1, wherein the component is a bodywork

component of a motor vehicle.

Page 3 of 8

Appl. No. 10/685,678 Amdt. dated November 12, 2004 Reply to Office Action dated August 11, 2004

Claim 7 (currently amended): The process as recited in claim 1, wherein the support material has a thickness of from 100 to 1200 µm. and

Claim 8 (original): The process as recited in claim 1, wherein the component includes a polymer material and the support material has a thickness of from 700 to 1200 μm .

Claim 9 (original): The process as recited in claim 1, wherein the component includes a metal and the support material has a thickness of from 50 to 300 μm .